

Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis

DRAFT

Model Year 2009 Basis with Tier 3 off-road engines

MCAQMD Operations

Pollutant	lbs/day																	Thresholds of Significance	
	Train 1	Train 2	Train 3	Train 4	Train Total	T1-Traffic Que	T2-Traffic Que	T3-Traffic Que	T4-Traffic Que	Traffic Que Total	T1-Disp Truck Travel	T2-Disp Truck Travel	T3-Disp Truck Travel	T4-Disp Truck Travel	Total Disp Truck Total	Solid Waste Transfer Operations	Total	lb/day	%of Threshold
Criteria Pollutant Emissions																			
ROG	0.246	0.240	0.914	0.000	1.399	0.003	0.013	0.098	0.000	0.114	2.726	7.487	41.314	0.000	51.527	0.000	-50.014	180	-28%
CO	4.015	3.913	14.930	0.000	22.858	0.015	0.079	0.572	0.000	0.665	19.267	52.907	291.956	0.000	364.129	0.000	-340.607	690	-49%
NOx	11.799	11.500	43.875	0.000	67.174	0.013	0.068	0.495	0.000	0.575	49.188	135.074	745.375	0.000	929.637	0.000	-861.888	42	-2052%
SOx	0.631	0.615	2.346	0.000	3.592	0.000	0.000	0.000	0.000	0.000	0.061	0.167	0.919	0.000	1.147	0.000	2.446	NA	NA
PM-10	0.287	0.280	1.066	0.000	1.633	0.000	0.000	0.002	0.000	0.002	1.790	4.915	27.121	0.000	33.826	0.000	-32.191	80	-40%
PM-2.5	0.264	0.257	0.981	0.000	1.502	0.000	0.000	0.002	0.000	0.002	1.646	4.519	24.938	0.000	31.103	0.000	-29.599	NA	NA
Toxics Emissions																			
Diesel PM	0.287	0.280	1.066	0.000	1.633	0.000	0.000	0.002	0.000	0.002	1.790	4.915	27.121	0.000	33.826	0.000	-32.191	NA	NA
Green House Gas Emissions																			
CH4	0.010	0.010	0.039	0.000	0.060	0.000	0.000	0.003	0.000	0.004	0.133	0.364	2.011	0.000	2.508	0.000	-2.445	NA	NA
CO2	1961.834	1912.007	7294.872	0.000	11168.712	0.923	4.969	36.156	0.000	42.048	6349.834	17436.938	96222.128	0.000	120008.900	0.000	-108798.140	NA	NA
CO ₂ -e	1962.053	1912.221	7295.688	0.000	11169.962	0.925	4.978	36.225	0.000	42.128	6352.621	17444.591	96264.362	0.000	120061.574	0.000	-108849.484	NA	NA

NSCAPCD Operations

Pollutant	tons/yr																	Thresholds of Significance	
	Train 1	Train 2	Train 3	Train 4	Train Total	T1-Traffic Que	T2-Traffic Que	T3-Traffic Que	T4-Traffic Que	Traffic Que Total	T1-Disp Truck Travel	T2-Disp Truck Travel	T3-Disp Truck Travel	T4-Disp Truck Travel	Total Disp Truck Travel	Solid Waste Transfer Operations	Total	ton/yr	%of Threshold
Criteria Pollutant Emissions																			
ROG	0.000	0.026	0.049	0.000	0.075	0.000	0.002	0.008	0.000	0.010	0.000	0.808	2.694	0.000	3.503	0.000	-3.417	40	-9%
CO	0.000	0.430	0.802	0.000	1.233	0.000	0.010	0.049	0.000	0.059	0.000	5.712	19.040	0.000	24.752	0.000	-23.460	100	-23%
NOx	0.000	1.264	2.358	0.000	3.622	0.000	0.009	0.043	0.000	0.051	0.000	14.583	48.610	0.000	63.193	0.000	-59.520	40	-149%
SOx	0.000	0.068	0.126	0.000	0.194	0.000	0.000	0.000	0.000	0.000	0.000	0.018	0.060	0.000	0.078	0.000	0.116	40	0.3%
PM-10	0.000	0.031	0.057	0.000	0.088	0.000	0.000	0.000	0.000	0.000	0.000	0.531	1.769	0.000	2.299	0.000	-2.211	15	-15%
PM-2.5	0.000	0.028	0.053	0.000	0.081	0.000	0.000	0.000	0.000	0.000	0.000	0.488	1.626	0.000	2.114	0.000	-2.033	NA	NA
Toxics Emissions																			
Diesel PM	0.000	0.031	0.057	0.000	0.088	0.000	0.000	0.000	0.000	0.000	0.000	0.531	1.769	0.000	2.299	0.000	-2.211	NA	NA
Green House Gas Emissions																			
CH4	0.000	0.001	0.002	0.000	0.003	0.000	0.000	0.000	0.000	0.000	0.000	0.039	0.131	0.000	0.171	0.000	-0.167	NA	NA
CO2	0.000	210.242	392.012	0.000	602.254	0.000	0.626	3.116	0.000	3.742	0.000	1882.551	6275.171	0.000	8157.723	0.000	-7551.727	NA	NA
CO ₂ -e	0.000	210.266	392.056	0.000	602.321	0.000	0.627	3.122	0.000	3.749	0.000	1883.378	6277.926	0.000	8161.303	0.000	-7555.233	NA	NA

Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis

DRAFT

BAAQMD Operations

Pollutant	lbs/day																Thresholds of Significance		
	Train 1	Train 2	Train 3	Train 4	Train Total	T1-Traffic Que	T2-Traffic Que	T3-Traffic Que	T4-Traffic Que	Traffic Que Total	T1-Disp Truck Travel	T2-Disp Truck Travel	T3-Disp Truck Travel	T4-Disp Truck Travel	Total Disp Truck Travel	Solid Waste Transfer Operations	Total	lb/day	%of Threshold
Criteria Pollutant Emissions																			
ROG	0.000	0.700	1.316	0.782	2.798	0.000	0.062	0.278	0.217	0.557	0.000	16.035	53.449	10.726	80.210	0.849	-76.006	80	-95%
CO	0.000	11.430	21.489	12.774	45.693	0.000	0.378	1.701	1.327	3.406	0.000	109.674	365.578	73.362	548.614	4.244	-495.271	NA	NA
NOx	0.000	33.590	63.150	37.541	134.281	0.000	0.340	1.532	1.195	3.067	0.000	289.836	966.121	193.874	1449.831	6.224	-1306.259	80	-1633%
SOx	0.000	1.796	3.377	2.007	7.180	0.000	0.000	0.001	0.001	0.002	0.000	0.340	1.133	0.227	1.700	0.566	6.049	NA	NA
PM-10	0.000	0.816	1.535	0.912	3.264	0.000	0.005	0.021	0.017	0.042	0.000	9.897	32.990	6.620	49.507	0.283	-45.918	80	-57%
PM-2.5	0.000	0.751	1.412	0.839	3.003	0.000	0.004	0.020	0.015	0.039	0.000	9.111	30.370	6.095	45.576	0.260	-42.274	NA	NA
Toxics Emissions																			
Diesel PM	0.000	0.816	1.535	0.912	3.264	0.000	0.005	0.021	0.017	0.042	0.000	9.897	32.990	6.620	49.507	0.283	-45.918	NA	NA
Green House Gas Emissions																			
CH4	0.000	0.030	0.056	0.033	0.119	0.000	0.003	0.012	0.010	0.025	0.000	0.850	2.832	0.568	4.250	0.265	-3.840	NA	NA
CO2	0.000	5584.828	10499.776	6241.842	22326.446	0.000	26.988	121.435	94.737	243.159	0.000	34688.521	115628.403	23203.457	173520.381	49800.000	-101150.776	NA	NA
CO ₂ -e	0.000	5585.454	10500.951	6242.541	22328.945	0.000	27.046	121.696	94.941	243.684	0.000	34706.361	115687.869	23215.391	173609.621	49805.575	-101231.417	NA	NA

Pollutant	tons/yr																Thresholds of Significance		
	Train 1	Train 2	Train 3	Train 4	Train Total	T1-Traffic Que	T2-Traffic Que	T3-Traffic Que	T4-Traffic Que	Traffic Que Total	T1-Disp Truck Travel	T2-Disp Truck Travel	T3-Disp Truck Travel	T4-Disp Truck Travel	Total Disp Truck Travel	Solid Waste Transfer Operations	Total	ton/yr	%of Threshold
Criteria Pollutant Emissions																			
ROG	0.000	0.109	0.205	0.122	0.436	0.000	0.010	0.043	0.034	0.087	0.000	2.501	8.338	1.673	12.513	0.132	-11.857	15	-79%
CO	0.000	1.783	3.352	1.993	7.128	0.000	0.059	0.265	0.207	0.531	0.000	17.109	57.030	11.444	85.584	0.662	-77.262	NA	NA
NOx	0.000	5.240	9.851	5.856	20.948	0.000	0.053	0.239	0.186	0.479	0.000	45.214	150.715	30.244	226.174	0.971	-203.776	15	-1359%
SOx	0.000	0.280	0.527	0.313	1.120	0.000	0.000	0.000	0.000	0.000	0.000	0.053	0.177	0.035	0.265	0.088	0.944	NA	NA
PM-10	0.000	0.127	0.239	0.142	0.509	0.000	0.001	0.003	0.003	0.007	0.000	1.544	5.146	1.033	7.723	0.044	-7.163	15	-48%
PM-2.5	0.000	0.117	0.220	0.131	0.468	0.000	0.001	0.003	0.002	0.006	0.000	1.421	4.738	0.951	7.110	0.041	-6.595	NA	NA
Toxics Emissions																			
Diesel PM	0.000	0.127	0.239	0.142	0.509	0.000	0.001	0.003	0.003	0.007	0.000	1.544	5.146	1.033	7.723	0.044	-7.163	NA	NA
Green House Gas Emissions																			
CH4	0.000	0.005	0.009	0.005	0.019	0.000	0.000	0.002	0.002	0.004	0.000	0.133	0.442	0.089	0.663	0.041	-0.599	NA	NA
CO2	0.000	871.233	1637.965	973.727	3482.926	0.000	4.210	18.944	14.779	37.933	0.000	5411.409	18038.031	3619.739	27069.179	7768.800	-15779.521	NA	NA
CO ₂ -e	0.000	871.331	1638.148	973.836	3483.315	0.000	4.219	18.985	14.811	38.015	0.000	5414.192	18047.308	3621.601	27083.101	7769.670	-15792.101	NA	NA

REDWOOD VALLEY TO WILLITS MERCHANDISE TRAIN

TRAIN OPERATIONS BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	10	10
max cars per train	10	10
Ave Cars per train	10	10
Length per car (feet)	67.583	67.583
Number of Engines	1	1
Length per engine (feet)	62.5	62.5
Train Length (feet)	738	738
Weight per Car (tons)	130	30
Cargo weight per car	100	0
Horse Power per Engine	2100	2100
Engine Load Factor (%)	60%	40%
Trip Distance (mi)	21.50	21.50
MCAQMD Portion (mi)	21.50	21.50
NSCAPCD Portion (mi)	0.00	0.00
BAAQMD Portion (mi)	0.00	0.00
Travel Time MCAQMP Portion (hr/day)	0.87	0.87
Travel Time NSCAPCD Portion (hr/day)	0.00	0.00
Travel Time BAAQMD Portion (hr/day)	0.00	0.00
Travel Time MCAQMP Portion (hr/yr)	271.13	271.13
Travel Time NSCAPCD Portion (hr/yr)	0.00	0.00
Travel Time BAAQMD Portion (hr/yr)	0.00	0.00

TRAIN EMISSIONS

Emission Factors ¹		MCAQMD Operations		NSCAPCD Operations		BAAQMD Operations	
Tier 3 (off-road engines)	g/bhp-hr	lbs/day	tons/yr	lbs/day	tons/yr	lbs/day	tons/yr
ROG ²	0.06	0.24	0.04	0.00	0.00	0.00	0.00
CO	0.98	3.94	0.62	0.00	0.00	0.00	0.00
NOx	2.88	11.59	1.81	0.00	0.00	0.00	0.00
SOx ³	0.154	0.62	0.10	0.00	0.00	0.00	0.00
PM-10	0.07	0.28	0.04	0.00	0.00	0.00	0.00
PM-2.5 ⁴	0.06	0.26	0.04	0.00	0.00	0.00	0.00
CH ₄ ⁵	0.003	0.01	0.00	0.00	0.00	0.00	0.00
CO ₂ ⁶	478.85	1926.47	300.53	0.00	0.00	0.00	0.00

- 1) Tier 3 emission factors based on published data provided by the locomotive manufacturer for N-ViroMotive with Cummins QSK19 Engine sets.
- 2) ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.
- 3) SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:

$$500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lb Sulfur} = 0.154 \text{ g/bhp-hr}$$
 Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).
- 4) A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM2.5 emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.
- 5) An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.
- 6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.

REDWOOD VALLEY TO WILLITS NORMAL FREIGHT

TRAFFIC QUEUING BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	10	10
max cars per train	10	10
Ave Cars per train	10	10
Length per car (feet)	67.583	67.583
Number of Engines	1	1
Length per engine (feet)	62.5	62.5
Train length (feet)	738	738
Crossing guard closure time (s/train)	22	22
MCAQMD Crossings Que Time (hr/train)	0.3930	0.3930
NSCAPCD Crossings Que Time (hr/train)	0.0000	0.0000
BAAQMD Crossings Que Time (hr/train)	0.0000	0.0000

Based on FRA requirements of 20 second pre-crossing signal control and 2 second post-crossing signal control

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMP Section Emissions		NSCAPCD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr	lbs/day	tons/yr
ROG	1.44E+00	2.50E-03	3.90E-04	0.00E+00	0.00E+00
CO	8.43E+00	1.46E-02	2.28E-03	0.00E+00	0.00E+00
NOx	7.29E+00	1.26E-02	1.97E-03	0.00E+00	0.00E+00
SOx	5.00E-03	8.66E-06	1.35E-06	0.00E+00	0.00E+00
PM-10	2.60E-02	4.51E-05	7.03E-06	0.00E+00	0.00E+00
PM-2.5	2.40E-02	4.16E-05	6.49E-06	0.00E+00	0.00E+00
CO2	5.33E+02	9.23E-01	1.44E-01	0.00E+00	0.00E+00
CH4	4.80E-02	8.32E-05	1.30E-05	0.00E+00	0.00E+00

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr
ROG	6.70E-01	0.00E+00	0.00E+00
CO	4.09E+00	0.00E+00	0.00E+00
NOx	3.69E+00	0.00E+00	0.00E+00
SOx	3.00E-03	0.00E+00	0.00E+00
PM-10	5.10E-02	0.00E+00	0.00E+00
PM-2.5	4.70E-02	0.00E+00	0.00E+00
CO2	2.92E+02	0.00E+00	0.00E+00
CH4	3.00E-02	0.00E+00	0.00E+00

Based on idling emissions (0 mph) from EMFAC2007

In accordance with BAAQMD CEQA Guidance recommended temperature basis, the Mean Summer Max for all pollutants except CO, and Mean Winter Minimum for CO, were applied for evaluating emissions with the EMFAC2007 program.

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

REDWOOD VALLEY TO WILLITS NORMAL FREIGHT

TRAIN OPERATIONS BASIS	Loaded trip	Return tip
Trains per day	1	1
Trains per year	312	312
Ave Cars per train	10	10
Gross weight per car (tons/car)	130	30
Cargo weight per car (tons/car)	100	0
Total daily cargo weight (tons/day)	1000	0
Total annual cargo weight (tons/yr)	312000	0
Average Truck Capacity (tons/truck)	25	0
Equivalent number of trucks (trucks/day)	40	40
Equivalent number of trucks (trucks/yr)	12480	12480
Trip Distance (mi)	21.50	21.50
MCAQMD Portion (mi)	21.50	21.50
NSCAPCD Portion (mi)	0.00	0.00
BAAQMD Portion (mi)	0.00	0.00

Based on 4 trucks per train car
assume trucks travel full one way and empty back
assume trucks travel full one way and empty back

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMD Section Emissions		NSCAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr	lbs/day	tons/yr
ROG	7.19E-01	2.73E+00	4.25E-01	0.00E+00	0.00E+00
CO	5.08E+00	1.93E+01	3.01E+00	0.00E+00	0.00E+00
NOx	1.30E+01	4.92E+01	7.67E+00	0.00E+00	0.00E+00
SOx	1.60E-02	6.07E-02	9.46E-03	0.00E+00	0.00E+00
PM-10	4.72E-01	1.79E+00	2.79E-01	0.00E+00	0.00E+00
PM-2.5	4.34E-01	1.65E+00	2.57E-01	0.00E+00	0.00E+00
CO2	1.67E+03	6.35E+03	9.91E+02	0.00E+00	0.00E+00
CH4	3.50E-02	1.33E-01	2.07E-02	0.00E+00	0.00E+00

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr
ROG	7.55E-01	0.00E+00	0.00E+00
CO	5.16E+00	0.00E+00	0.00E+00
NOx	1.36E+01	0.00E+00	0.00E+00
SOx	1.60E-02	0.00E+00	0.00E+00
PM-10	4.66E-01	0.00E+00	0.00E+00
PM-2.5	4.29E-01	0.00E+00	0.00E+00
CO2	1.63E+03	0.00E+00	0.00E+00
CH4	4.00E-02	0.00E+00	0.00E+00

Based on average maximum summertime temperature for all compounds except CO. Based on average minimum wintertime temperature for CO.
78207/T1-DIS TRUCKS -REDWD TO WILLITS

LOMBARD TO REDWOOD VALLEY MERCHANDISE TRAIN

TRAIN OPERATIONS BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	10	10
max cars per train	25	25
Ave Cars per train	18	18
Length per car (feet)	67.583	67.583
Number of Engines	1	1
Length per engine (feet)	62.5	62.5
Train Length (feet)	1279	1279
Weight per Car (tons)	130	30
Cargo weight per car	100	0
Horse Power per Engine	2100	2100
Engine Load Factor (%)	60%	40%
Trip Distance (mi)	122.40	122.40
MCAQMD Portion (mi)	32.80	32.80
NSCAPCD Portion (mi)	22.70	22.70
BAAQMD Portion (mi)	66.90	66.90
Travel Time MCAQMP Portion (hr/day)	0.85	0.85
Travel Time NSCAPCD Portion (hr/day)	0.58	0.58
Travel Time BAAQMD Portion (hr/day)	2.46	2.46
Travel Time MCAQMP Portion (hr/yr)	266.60	266.60
Travel Time NSCAPCD Portion (hr/yr)	182.21	182.21
Travel Time BAAQMD Portion (hr/yr)	768.58	768.58

TRAIN EMISSIONS

Emission Factors ¹		MCAQMD Operations		NSCAPCD Operations		BAAQMD Operations	
Tier 3 (off-road engines)	g/bhp-hr	lbs/day	tons/yr	lbs/day	tons/yr	lbs/day	tons/yr
ROG ²	0.06	0.24	0.04	0.16	0.03	0.68	0.11
CO	0.98	3.88	0.60	2.65	0.41	11.18	1.74
NOx	2.88	11.39	1.78	7.79	1.21	32.85	5.12
SOx ³	0.154	0.61	0.10	0.42	0.06	1.76	0.27
PM-10	0.07	0.28	0.04	0.19	0.03	0.80	0.12
PM-2.5 ⁴	0.06	0.25	0.04	0.17	0.03	0.73	0.11
CH ₄ ⁵	0.003	0.01	0.00	0.01	0.00	0.03	0.00
CO ₂ ⁶	478.85	1894.32	295.51	1294.66	201.97	5461.05	851.92

1) Tier 3 emission factors based on published data provided by the locomotive manufacturer for N-ViroMotive with Cummins QSK19 Engine sets.

2) ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.

3) SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:

$$500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lb Sulfur} = 0.154 \text{ g/bhp-hr}$$

Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).

4) A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM2.5 emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.

5) An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.

6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.

REDWOOD VALLEY TO LOMBARD NORMAL FREIGHT

TRAFFIC QUEUING BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	10	10
max cars per train	25	25
Ave Cars per train	18	18
Length per car (feet)	67.583	67.583
Number of Engines	1	1
Length per engine (feet)	62.5	62.5
Train length (feet)	1,279	1,279
Crossing guard closure time (s/train)	22	22
MCAQMD Crossings Que Time (hr/train)	2.1152	2.1152
NSCAPCD Crossings Que Time (hr/train)	1.7077	1.7077
BAAQMD Crossings Que Time (hr/train)	20.9421	20.9421

Based on FRA requirements of 20 second pre-crossing signal control and 2 second post-crossing signal control

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMP Section Emissions		NSCAPCD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr	lbs/day	tons/yr
ROG	1.44E+00	1.35E-02	2.10E-03	1.09E-02	1.69E-03
CO	8.43E+00	7.86E-02	1.23E-02	6.34E-02	9.90E-03
NOx	7.29E+00	6.80E-02	1.06E-02	5.49E-02	8.56E-03
SOx	5.00E-03	4.66E-05	7.27E-06	3.76E-05	5.87E-06
PM-10	2.60E-02	2.42E-04	3.78E-05	1.96E-04	3.05E-05
PM-2.5	2.40E-02	2.24E-04	3.49E-05	1.81E-04	2.82E-05
CO2	5.33E+02	4.97E+00	7.75E-01	4.01E+00	6.26E-01
CH4	4.80E-02	4.48E-04	6.98E-05	3.61E-04	5.64E-05

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr
ROG	6.70E-01	6.19E-02	9.65E-03
CO	4.09E+00	3.78E-01	5.90E-02
NOx	3.69E+00	3.40E-01	5.31E-02
SOx	3.00E-03	2.77E-04	4.32E-05
PM-10	5.10E-02	4.71E-03	7.35E-04
PM-2.5	4.70E-02	4.34E-03	6.77E-04
CO2	2.92E+02	2.70E+01	4.21E+00
CH4	3.00E-02	2.77E-03	4.32E-04

Based on idling emissions (0 mph) from EMFAC2007

In accordance with BAAQMD CEQA Guidance recommended temperature basis, the Mean Summer Max for all pollutants except CO, and Mean Winter Minimum for CO, were applied for evaluating emissions with the EMFAC2007 program.

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

LOMBARD TO REDWOOD VALLEY NORMAL FREIGHT

TRAIN OPERATIONS BASIS	Loaded trip	Return tip
Trains per day	1	1
Trains per year	312	312
Ave Cars per train	18	18
Gross weight per car (tons/car)	130	30
Cargo weight per car (tons/car)	100	0
Total daily cargo weight (tons/day)	1800	0
Total annual cargo weight (tons/yr)	561600	0
Average Truck Capacity (tons/truck)	25	0
Equivalent number of trucks (trucks/day)	72	72
Equivalent number of trucks (trucks/yr)	22464	22464
Trip Distance (mi)	122.40	122.40
MCAQMD Portion (mi)	32.80	32.80
NSCAPCD Portion (mi)	22.70	22.70
BAAQMD Portion (mi)	66.90	66.90

Based on 4 trucks per train car
assume trucks travel full one way and empty back
assume trucks travel full one way and empty back

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMD Section Emissions		NSCAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr	lbs/day	tons/yr
ROG	7.19E-01	7.49E+00	1.17E+00	5.18E+00	8.08E-01
CO	5.08E+00	5.29E+01	8.25E+00	3.66E+01	5.71E+00
NOx	1.30E+01	1.35E+02	2.11E+01	9.35E+01	1.46E+01
SOx	1.60E-02	1.67E-01	2.60E-02	1.15E-01	1.80E-02
PM-10	4.72E-01	4.91E+00	7.67E-01	3.40E+00	5.31E-01
PM-2.5	4.34E-01	4.52E+00	7.05E-01	3.13E+00	4.88E-01
CO2	1.67E+03	1.74E+04	2.72E+03	1.21E+04	1.88E+03
CH4	3.50E-02	3.64E-01	5.69E-02	2.52E-01	3.93E-02

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr
ROG	7.55E-01	1.60E+01	2.50E+00
CO	5.16E+00	1.10E+02	1.71E+01
NOx	1.36E+01	2.90E+02	4.52E+01
SOx	1.60E-02	3.40E-01	5.30E-02
PM-10	4.66E-01	9.90E+00	1.54E+00
PM-2.5	4.29E-01	9.11E+00	1.42E+00
CO2	1.63E+03	3.47E+04	5.41E+03
CH4	4.00E-02	8.50E-01	1.33E-01

Based on average maximum summertime temperature for all compounds except CO. Based on average minimum wintertime temperature for CO.
78207/T2-DIS TRUCKS -LOMBARD TO REDWD

LOMBARD TO WILLITS MERCHANDISE TRAIN

TRAIN OPERATIONS BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	60	60
max cars per train	60	60
Ave Cars per train	60	60
Length per car (feet)	67.583	67.583
Number of Engines	2	2
Length per engine (feet)	62.5	62.5
Train Length (feet)	4180	4180
Weight per Car (tons)	130	30
Cargo weight per car	100	0
Horse Power per Engine	2100	2100
Engine Load Factor (%)	70%	25%
Trip Distance (mi)	143.90	143.90
MCAQMD Portion (mi)	54.30	54.30
NSCAPCD Portion (mi)	22.70	22.70
BAAQMD Portion (mi)	66.90	66.90
Travel Time MCAQMP Portion (hr/day)	1.72	1.72
Travel Time NSCAPCD Portion (hr/day)	0.58	0.58
Travel Time BAAQMD Portion (hr/day)	2.46	2.46
Travel Time MCAQMP Portion (hr/yr)	537.73	537.73
Travel Time NSCAPCD Portion (hr/yr)	182.21	182.21
Travel Time BAAQMD Portion (hr/yr)	768.58	768.58

TRAIN EMISSIONS

Emission Factors ¹		MCAQMD Operations		NSCAPCD Operations		BAAQMD Operations	
Tier 3 (off-road engines)	g/bhp-hr	lbs/day	tons/yr	lbs/day	tons/yr	lbs/day	tons/yr
ROG ²	0.06	0.91	0.14	0.31	0.05	1.30	0.20
CO	0.98	14.86	2.32	5.03	0.79	21.24	3.31
NOx	2.88	43.66	6.81	14.79	2.31	62.41	9.74
SOx ³	0.154	2.33	0.36	0.79	0.12	3.34	0.52
PM-10	0.07	1.06	0.17	0.36	0.06	1.52	0.24
PM-2.5 ⁴	0.06	0.98	0.15	0.33	0.05	1.40	0.22
CH ₄ ⁵	0.003	0.04	0.01	0.01	0.00	0.06	0.01
CO ₂ ⁶	478.85	7259.51	1132.48	2459.85	383.74	10376.00	1618.66

- 1) Tier 3 emission factors based on published data provided by the locomotive manufacturer for N-ViroMotive with Cummins QSK19 Engine sets.
- 2) ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.
- 3) SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:
 $500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lbs Sulfur} = 0.154 \text{ g/bhp-hr}$
 Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).
- 4) A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM2.5 emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.
- 5) An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.
- 6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.

LOMBARD TO WILLITS NORMAL FREIGHT

TRAFFIC QUEUING BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	60	60
max cars per train	60	60
Ave Cars per train	60	60
Length per car (feet)	67.583	67.583
Number of Engines	2	2
Length per engine (feet)	62.5	62.5
Train length (feet)	4,180	4,180
Crossing guard closure time (s/train)	22	22
MCAQMD Crossings Que Time (hr/train)	15.3921	15.3921
NSCAPCD Crossings Que Time (hr/train)	8.5028	8.5028
BAAQMD Crossings Que Time (hr/train)	94.2306	94.2306

Based on FRA requirements of 20 second pre-crossing signal control and 2 second post-crossing signal control

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMP Section Emissions		NSCAPCD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr	lbs/day	tons/yr
ROG	1.44E+00	9.79E-02	1.53E-02	5.41E-02	8.44E-03
CO	8.43E+00	5.72E-01	8.92E-02	3.16E-01	4.93E-02
NOx	7.29E+00	4.95E-01	7.72E-02	2.73E-01	4.26E-02
SOx	5.00E-03	3.39E-04	5.29E-05	1.87E-04	2.92E-05
PM-10	2.60E-02	1.76E-03	2.75E-04	9.75E-04	1.52E-04
PM-2.5	2.40E-02	1.63E-03	2.54E-04	9.00E-04	1.40E-04
CO2	5.33E+02	3.62E+01	5.64E+00	2.00E+01	3.12E+00
CH4	4.80E-02	3.26E-03	5.08E-04	1.80E-03	2.81E-04

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr
ROG	6.70E-01	2.78E-01	4.34E-02
CO	4.09E+00	1.70E+00	2.65E-01
NOx	3.69E+00	1.53E+00	2.39E-01
SOx	3.00E-03	1.25E-03	1.94E-04
PM-10	5.10E-02	2.12E-02	3.31E-03
PM-2.5	4.70E-02	1.95E-02	3.05E-03
CO2	2.92E+02	1.21E+02	1.89E+01
CH4	3.00E-02	1.25E-02	1.94E-03

Based on idling emissions (0 mph) from EMFAC2007

In accordance with BAAQMD CEQA Guidance recommended temperature basis, the Mean Summer Max for all pollutants except CO, and Mean Winter Minimum for CO, were applied for evaluating emissions with the EMFAC2007 program.

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

LOMBARD TO WILLITS NORMAL FREIGHT

TRAIN OPERATIONS BASIS	Loaded trip	Return tip
Trains per day	1	1
Trains per year	312	312
Ave Cars per train	60	60
Gross weight per car (tons/car)	130	30
Cargo weight per car (tons/car)	100	0
Total daily cargo weight (tons/day)	6000	0
Total annual cargo weight (tons/yr)	1872000	0
Average Truck Capacity (tons/truck)	25	0
Equivalent number of trucks (trucks/day)	240	240
Equivalent number of trucks (trucks/yr)	74880	74880
Trip Distance (mi)	143.90	143.90
MCAQMD Portion (mi)	54.30	54.30
NSCAPCD Portion (mi)	22.70	22.70
BAAQMD Portion (mi)	66.90	66.90

Based on 4 trucks per train car
assume trucks travel full one way and empty back
assume trucks travel full one way and empty back

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMD Section Emissions		NSCAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr	lbs/day	tons/yr
ROG	7.19E-01	4.13E+01	6.44E+00	1.73E+01	2.69E+00
CO	5.08E+00	2.92E+02	4.55E+01	1.22E+02	1.90E+01
NOx	1.30E+01	7.45E+02	1.16E+02	3.12E+02	4.86E+01
SOx	1.60E-02	9.19E-01	1.43E-01	3.84E-01	6.00E-02
PM-10	4.72E-01	2.71E+01	4.23E+00	1.13E+01	1.77E+00
PM-2.5	4.34E-01	2.49E+01	3.89E+00	1.04E+01	1.63E+00
CO2	1.67E+03	9.62E+04	1.50E+04	4.02E+04	6.28E+03
CH4	3.50E-02	2.01E+00	3.14E-01	8.41E-01	1.31E-01

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr
ROG	7.55E-01	5.34E+01	8.34E+00
CO	5.16E+00	3.66E+02	5.70E+01
NOx	1.36E+01	9.66E+02	1.51E+02
SOx	1.60E-02	1.13E+00	1.77E-01
PM-10	4.66E-01	3.30E+01	5.15E+00
PM-2.5	4.29E-01	3.04E+01	4.74E+00
CO2	1.63E+03	1.16E+05	1.80E+04
CH4	4.00E-02	2.83E+00	4.42E-01

Based on average maximum summertime temperature for all compounds except CO. Based on average minimum wintertime temperature for CO.
78207/T3-DIS TRUCKS -LOMB TO WILLITS

LOMBARD TO SANTA ROSA SOLID WASTE TRAIN

TRAIN OPERATIONS BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	60	60
max cars per train	60	60
Ave Cars per train	60	60
Length per car (feet)	67.583	67.583
Number of Engines	2	2
Length per engine (feet)	62.5	62.5
Train Length (feet)	4180	4180
Weight per Car (tons)	70	30
Cargo weight per car	40	0
Horse Power per Engine	2100	2100
Engine Load Factor (%)	40%	25%
Trip Distance (mi)	53.70	53.70
MCAQMD Portion (mi)	0.00	0.00
NSCAPCD Portion (mi)	0.00	0.00
BAAQMD Portion (mi)	53.70	53.70
Travel Time MCAQMP Portion (hr/day)	0.00	0.00
Travel Time NSCAPCD Portion (hr/day)	0.00	0.00
Travel Time BAAQMD Portion (hr/day)	2.12	2.12
Travel Time MCAQMP Portion (hr/yr)	0.00	0.00
Travel Time NSCAPCD Portion (hr/yr)	0.00	0.00
Travel Time BAAQMD Portion (hr/yr)	662.34	662.34

TRAIN EMISSIONS

Emission Factors ¹		MCAQMD Operations		NSCAPCD Operations		BAAQMD Operations	
Tier 3 (off-road engines)	g/bhp-hr	lbs/day	tons/yr	lbs/day	tons/yr	lbs/day	tons/yr
ROG ²	0.06	0.00	0.00	0.00	0.00	0.77	0.12
CO	0.98	0.00	0.00	0.00	0.00	12.52	1.95
NOx	2.88	0.00	0.00	0.00	0.00	36.80	5.74
SOx ³	0.154	0.00	0.00	0.00	0.00	1.97	0.31
PM-10	0.07	0.00	0.00	0.00	0.00	0.89	0.14
PM-2.5 ⁴	0.06	0.00	0.00	0.00	0.00	0.82	0.13
CH ₄ ⁵	0.003	0.00	0.00	0.00	0.00	0.03	0.01
CO ₂ ⁶	478.85	0.00	0.00	0.00	0.00	6118.07	954.42

1) Tier 3 emission factors based on published data provided by the locomotive manufacturer for N-ViroMotive with Cummins QSK19 Engine sets.

2) ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.

3) SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:

$$500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lb Sulfur} = 0.154 \text{ g/bhp-hr}$$

Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).

4) A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM2.5 emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.

5) An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.

6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.

LOMBARD TO SANTA ROSA SOLID WASTE TRAIN

TRAFFIC QUEUING BASIS	Loaded trip	Return trip
Trains per day	1	1
Days per week	6	6
Trains per week	6	6
Weeks per Year	52	52
Trains per year	312	312
Min cars per train	60	60
max cars per train	60	60
Ave Cars per train	60	60
Length per car (feet)	67.583	67.583
Number of Engines	2	2
Length per engine (feet)	62.5	62.5
Train length (feet)	4,180	4,180
Crossing guard closure time (s/train)	22	22
MCAQMD Crossings Que Time (hr/train)	0.0000	0.0000
NSCAPCD Crossings Que Time (hr/train)	0.0000	0.0000
BAAQMD Crossings Que Time (hr/train)	73.5139	73.5139

Based on FRA requirements of 20 second pre-crossing signal control and 2 second post-crossing signal control

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMP Section Emissions		NSCAPCD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr	lbs/day	tons/yr
ROG	1.44E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CO	8.43E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NOx	7.29E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
SOx	5.00E-03	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PM-10	2.60E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PM-2.5	2.40E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CO2	5.33E+02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CH4	4.80E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/idle-hr	lbs/day	tons/yr
ROG	6.70E-01	2.17E-01	3.39E-02
CO	4.09E+00	1.33E+00	2.07E-01
NOx	3.69E+00	1.20E+00	1.86E-01
SOx	3.00E-03	9.72E-04	1.52E-04
PM-10	5.10E-02	1.65E-02	2.58E-03
PM-2.5	4.70E-02	1.52E-02	2.38E-03
CO2	2.92E+02	9.47E+01	1.48E+01
CH4	3.00E-02	9.72E-03	1.52E-03

Based on idling emissions (0 mph) from EMFAC2007

In accordance with BAAQMD CEQA Guidance recommended temperature basis, the Mean Summer Max for all pollutants except CO, and Mean Winter Minimum for CO, were applied for evaluating emissions with the EMFAC2007 program.

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

LOMBARD TO SANTA ROSA SOLID WASTE

TRAIN OPERATIONS BASIS	Loaded trip	Return tip
Trains per day	1	1
Trains per year	312	312
Ave Cars per train	60	60
Gross weight per car (tons/car)	70	30
Cargo weight per car (tons/car)	40	0
Total daily cargo weight (tons/day)	2400	0
Total annual cargo weight (tons/yr)	748800	0
Average Truck Capacity (tons/truck)	40	0
Equivalent number of trucks (trucks/day)	60	60
Equivalent number of trucks (trucks/yr)	18720	18720
Trip Distance (mi)	53.70	53.70
MCAQMD Portion (mi)	0.00	0.00
NSCAPCD Portion (mi)	0.00	0.00
BAAQMD Portion (mi)	53.70	53.70

Based on 1 truck per train car
assume trucks travel full one way and empty back
assume trucks travel full one way and empty back

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(NORTH COAST AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		MCAQMD Section Emissions		NSCAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr	lbs/day	tons/yr
ROG	7.19E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CO	5.08E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NOx	1.30E+01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
SOx	1.60E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PM-10	4.72E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
PM-2.5	4.34E-01	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CO2	1.67E+03	0.00E+00	0.00E+00	0.00E+00	0.00E+00
CH4	3.50E-02	0.00E+00	0.00E+00	0.00E+00	0.00E+00

HHDT EMISSIONS (AVERAGE SPEED OF 45 MPH)-(BAY AREA AIR BASIN EMFAC2007 EMISSION FACTORS)

Emission Factors		BAAQMD Section Emissions	
Model Year 2009 (current)	gr/mi	lbs/day	tons/yr
ROG	7.55E-01	1.07E+01	1.67E+00
CO	5.16E+00	7.34E+01	1.14E+01
NOx	1.36E+01	1.94E+02	3.02E+01
SOx	1.60E-02	2.27E-01	3.55E-02
PM-10	4.66E-01	6.62E+00	1.03E+00
PM-2.5	4.29E-01	6.09E+00	9.51E-01
CO2	1.63E+03	2.32E+04	3.62E+03
CH4	4.00E-02	5.68E-01	8.86E-02

Based on average maximum summertime temperature for all compounds except CO. Based on average minimum wintertime temperature for CO.
78207/T4-DIS TRUCKS -LOMBARD TO SROSA

Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis

DRAFT

City	Crossing Street Name	Mile Post	Distance Miles	Speed (MPH)					Speed (mph)	Seg Travel Time (hr)	Train 1	Gate Closure Time (s)			Approach Traffic Vol. (veh/hr)		Number of Lanes	Saturation Flow (veh/hr-lane)	T-1 Vehicle Delay (veh-hr)	T-2 Vehicle Delay (veh-hr)	T-3 Vehicle Delay (veh-hr)	T-4 Vehicle Delay (veh-hr)	
				10	15	20	25	35				40	Train 2	Train 3	Train 4	Approach Traffic Vol. D1							Approach Traffic Vol. D2
Lombard to Willits	Lombard to Redwood Valley	Lombard	1	Green Island Rd.	0.75	0.75				1	20	0.0375	65.60	164.50	164.50	419	419	1/1	1800	0.000	0.181	1.140	1.140
		2	Milton Rd.	3.04	2.29	1				10	0.2290	109.20	307.00	307.00	419	419	1/1	1800	0.000	0.503	3.972	3.972	
		3	Skaggs Island Rd.	6.69	3.65					35	0.1043	46.92	103.43	103.43	419	419	1/1	1800	0.000	0.093	0.451	0.451	
		4	SR 12/121 Cameros Hwy.	10.57	3.88		1			15	0.2587	176.55	308.41	308.41	1208	1195	1/1	1800	0.000	8.892	26.525	26.525	
		5	Roadway Rd.	13.63	3.06					35	0.0937	46.92	103.43	103.43	419	419	1/1	1800	0.000	0.093	0.451	0.451	
		6	SR 37 Sears Point Rd.	18.08	4.45					35	0.1271	46.92	103.43	103.43	1110	856	1/1	1800	0.000	0.384	1.869	1.869	
		7	Reclamation Rd.	20.14	2.06					35	0.0589	46.92	103.43	103.43	419	419	1/1	1800	0.000	0.093	0.451	0.451	
		8	(Roughly MP 20)	20.53	0.39					35	0.0111	46.92	103.43	103.43	419	419	1/1	1800	0.000	0.093	0.451	0.451	
		9	Port Sonoma Rd.	21.81	1.28					35	0.0366	46.92	103.43	103.43	419	419	1/1	1800	0.000	0.093	0.451	0.451	
		10	Grandview Ave.	22.86	1.05					10	0.1050	109.20	307.00	307.00	419	419	1/1	1800	0.000	0.503	3.972	3.972	
		11	Parking Lot Access	23.09	0.23					10	0.0233	109.20	307.00	307.00	419	419	1/1	1800	0.000	0.503	3.972	3.972	
		12	Stone Tree Ln.	23.26	0.17					10	0.0170	109.20	307.00	307.00	419	419	1/1	1800	0.000	0.503	3.972	3.972	
		13	Hanna Ranch Rd.	25.9	2.64					15	0.1760	80.14	212.00	212.00	419	419	1/1	1800	0.000	0.271	1.894	1.894	
		14	Grant Ave.	27.9	2					40	0.0500	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		15	Olive Ave.	28.1	0.2					40	0.0050	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		16	Golden Gate Place	28.35	0.25					40	0.0063	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		17	Rough Creek Place	28.5	0.15					40	0.0037	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		18	Country Dump Rd.	31.98	3.48					40	0.0870	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		19	Hoopar St.	38.3	6.32					25	0.2528	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		20	D St.	38.5	0.2					25	0.0080	56.88	136.00	136.00	666	737	1/1	1800	0.000	0.288	1.645	1.645	
		21	Washington St.	38.6	0.1					25	0.0040	56.88	136.00	136.00	1250	1851	2/2	1800	0.000	0.715	4.085	4.085	
		22	Lakeville St.	38.8	0.2					25	0.0080	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		23	W. Payran St.	39.2	0.4					25	0.0160	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		24	South Point Blvd.	40.4	1.1					40	0.0210	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		25	N. McDowell Blvd.	40.7	0.3					40	0.0075	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		26	Corona Rd.	41.1	0.4					40	0.0100	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		27	Ely Rd.	42.2	1.1					40	0.0275	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		28	Main St.	43.3	1.1					40	0.0275	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		29	Adobe Rd.	43.6	0.3					40	0.0075	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		30	E. Railroad Ave.	44.8	1.2					40	0.0480	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		31	E. Cotati Ave.	46.1	1.3					25	0.0520	56.88	136.00	136.00	1036	1047	2/2	1800	0.000	0.366	2.091	2.091	
		32	Southwest Blvd.	46.8	0.7					40	0.0175	43.80	93.25	93.25	823	930	2/2	1800	0.000	0.172	0.779	0.779	
		33	Rohmert Park Expy.	47.4	0.6					40	0.0150	43.80	93.25	93.25	1398	1287	2/2	1800	0.000	0.317	1.439	1.439	
		34	Golf Course Dr.	48.5	1.1					40	0.0275	43.80	93.25	93.25	1191	890	2/2	1800	0.000	0.219	0.994	0.994	
		35	Science Ave.	49.4	0.9					40	0.0225	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		36	Todd Rd.	50.3	0.9					40	0.0225	43.80	93.25	93.25	854	733	1/1	1800	0.000	0.168	0.759	0.759	
		37	W. Robles Ave.	50.8	0.5					40	0.0125	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		38	Bellvue Ave.	51.3	0.5					40	0.0125	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		39	Hearn Ave.	52.2	0.9					40	0.0225	43.80	93.25	93.25	1061	1460	2/2	1800	0.000	0.293	1.329	1.329	
		40	W. Barham Ave.	53	0.8					40	0.0200	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		41	Sebastopol Rd.	53.4	0.4					25	0.0160	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
42	3rd St.	53.7	0.3					25	0.0120	56.88	136.00	136.00	695	869	2/2	1800	0.000	0.251	1.432	1.432			
Sub-Total (Lombard to Santa Rosa)				63.7	4	2	1	9	2	123	2.123	25.29564297	56.88	136.00	136.00	419	419	1/1	1800	0.000	16.686	73.514	73.514
Lombard to Willits	Lombard to Redwood Valley	Lombard	43	6th St.	53.8	0.1				1	0.0040	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		44	7th St.	53.9	0.1					1	0.0040	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		45	8th St.	54	0.1					1	0.0040	56.88	136.00	136.00	419	419	1/1	1800	0.000	0.136	0.779	0.779	
		46	9th St.	54.1	0.1					1	0.0040	56.88	136.00	136.00	824	636	1/1	1800	0.000	0.312	1.786	1.786	
		47	College Ave.	54.4	0.3					1	0.0120	56.88	136.00	136.00	1259	1240	2/2	1800	0.000	0.478	2.731	2.731	
		48	Guerneville Rd.	55.3	0.9					1	0.0225	43.80	93.25	93.25	1967	1873	2/2	1800	0.000	0.610	2.765	2.765	
		49	W. Steele Ln.	55.6	0.3					1	0.0075	43.80	93.25	93.25	727	592	1/1	1800	0.000	0.168	0.759	0.759	
		50	Placer Rd.	56.3	0.7					1	0.0175	43.80	93.25	93.25	1639	1446	2/2	1800	0.000	0.402	1.820	1.820	
		51	San Miguel Ave.	56.8	0.5					1	0.0125	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		52	Fulton Rd.	58.5	1.7					1	0.0425	43.80	93.25	93.25	1091	1163	1/1	1800	0.000	0.448	2.032	2.032	
		53	River Rd.	58.8	0.3					1	0.0075	43.80	93.25	93.25	904	811	1/1	1800	0.000	0.203	0.920	0.920	
		54	Airport Blvd.	59.9	1.1					1	0.0275	43.80	93.25	93.25	833	1084	1/1	1800	0.000	0.216	1.434	1.434	
		55	Aviation Blvd.	60.2	0.3					1	0.0075	43.80	93.25	93.25	747	701	1/1	1800	0.000	0.179	0.814	0.814	
		56	Shiloh Rd.	61.1	0.9					1	0.0225	43.80	93.25	93.25	878	896	1/1	1800	0.000	0.259	1.174	1.174	
		57	Mitchell Ln.	61.7	0.6					1	0.0150	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		58	Windsor River Rd.	62.9	1.2					1	0.0300	43.80	93.25	93.25	419	419	1/1	1800	0.000	0.081	0.366	0.366	
		59	Starr Rd.	63.8	0.9					1	0.												

Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis

DRAFT

MCAQMD

Pollutant	Emission Factor (g/bhp-hr)	Power ¹ (bhp)	Time (hr/stop)	Stops per train ⁷				Trains		Cumulative Emissions (lbs/day)				Cumulative Emissions (tpy)			
				T1	T2	T3	T4	(trains per day)	(trains per year)	T1	T2	T3	T4	T1	T2	T3	T4
ROG ²	0.06	67	0.25	2	1	2	0	1	312	4.43E-03	2.22E-03	4.43E-03	0.00E+00	6.91E-04	3.46E-04	6.91E-04	0.00E+00
CO	0.98	67	0.25	2	1	2	0	1	312	7.24E-02	3.62E-02	7.24E-02	0.00E+00	1.13E-02	5.65E-03	1.13E-02	0.00E+00
NOx	2.88	67	0.25	2	1	2	0	1	312	2.13E-01	1.06E-01	2.13E-01	0.00E+00	3.32E-02	1.66E-02	3.32E-02	0.00E+00
SOx ³	0.154	67	0.25	2	1	2	0	1	312	1.14E-02	5.69E-03	1.14E-02	0.00E+00	1.77E-03	8.87E-04	1.77E-03	0.00E+00
PM-10 (Diesel Particulate)	0.07	67	0.25	2	1	2	0	1	312	5.17E-03	2.58E-03	5.17E-03	0.00E+00	8.06E-04	4.03E-04	8.06E-04	0.00E+00
PM-2.5 ⁴	0.06	67	0.25	2	1	2	0	1	312	4.76E-03	2.38E-03	4.76E-03	0.00E+00	7.42E-04	3.71E-04	7.42E-04	0.00E+00
CH ₄ ⁵	0.003	67	0.25	2	1	2	0	1	312	1.89E-04	9.43E-05	1.89E-04	0.00E+00	2.94E-05	1.47E-05	2.94E-05	0.00E+00
CO ₂ ⁶	478.85	67	0.25	2	1	2	0	1	312	3.54E+01	1.77E+01	3.54E+01	0.00E+00	5.52E+00	2.76E+00	5.52E+00	0.00E+00

NSCAPCD

Pollutant	Emission Factor (g/bhp-hr)	Power ¹ (bhp)	Time (hr/stop)	Stops per train ⁷				Trains		Cumulative Emissions (lbs/day)				Cumulative Emissions (tpy)			
				T1	T2	T3	T4	(trains per day)	(trains per year)	T1	T2	T3	T4	T1	T2	T3	T4
ROG ²	0.06	67	0.25	0	3	3	0	1	312	0.00E+00	6.65E-03	6.65E-03	0.00E+00	0.00E+00	1.04E-03	1.04E-03	0.00E+00
CO	0.98	67	0.25	0	3	3	0	1	312	0.00E+00	1.09E-01	1.09E-01	0.00E+00	0.00E+00	1.69E-02	1.69E-02	0.00E+00
NOx	2.88	67	0.25	0	3	3	0	1	312	0.00E+00	3.19E-01	3.19E-01	0.00E+00	0.00E+00	4.98E-02	4.98E-02	0.00E+00
SOx ³	0.154	67	0.25	0	3	3	0	1	312	0.00E+00	1.71E-02	1.71E-02	0.00E+00	0.00E+00	2.66E-03	2.66E-03	0.00E+00
PM-10 (Diesel Particulate)	0.07	67	0.25	0	3	3	0	1	312	0.00E+00	7.75E-03	7.75E-03	0.00E+00	0.00E+00	1.21E-03	1.21E-03	0.00E+00
PM-2.5 ⁴	0.06	67	0.25	0	3	3	0	1	312	0.00E+00	7.13E-03	7.13E-03	0.00E+00	0.00E+00	1.11E-03	1.11E-03	0.00E+00
CH ₄ ⁵	0.003	67	0.25	0	3	3	0	1	312	0.00E+00	2.83E-04	2.83E-04	0.00E+00	0.00E+00	4.41E-05	4.41E-05	0.00E+00
CO ₂ ⁶	478.85	67	0.25	0	3	3	0	1	312	0.00E+00	5.30E+01	5.30E+01	0.00E+00	0.00E+00	8.28E+00	8.28E+00	0.00E+00

BAAQMD

Pollutant	Emission Factor (g/bhp-hr)	Power ¹ (bhp)	Time (hr/stop)	Stops per train ⁷				Trains		Cumulative Emissions (lbs/day)				Cumulative Emissions (tpy)			
				T1	T2	T3	T4	(trains per day)	(trains per year)	T1	T2	T3	T4	T1	T2	T3	T4
ROG ²	0.06	67	0.25	0	7	7	7	1	312	0.00E+00	1.55E-02	1.55E-02	1.55E-02	0.00E+00	2.42E-03	2.42E-03	2.42E-03
CO	0.98	67	0.25	0	7	7	7	1	312	0.00E+00	2.53E-01	2.53E-01	2.53E-01	0.00E+00	3.95E-02	3.95E-02	3.95E-02
NOx	2.88	67	0.25	0	7	7	7	1	312	0.00E+00	7.44E-01	7.44E-01	7.44E-01	0.00E+00	1.16E-01	1.16E-01	1.16E-01
SOx ³	0.154	67	0.25	0	7	7	7	1	312	0.00E+00	3.98E-02	3.98E-02	3.98E-02	0.00E+00	6.21E-03	6.21E-03	6.21E-03
PM-10 (Diesel Particulate)	0.07	67	0.25	0	7	7	7	1	312	0.00E+00	1.81E-02	1.81E-02	1.81E-02	0.00E+00	2.82E-03	2.82E-03	2.82E-03
PM-2.5 ⁴	0.06	67	0.25	0	7	7	7	1	312	0.00E+00	1.66E-02	1.66E-02	1.66E-02	0.00E+00	2.60E-03	2.60E-03	2.60E-03
CH ₄ ⁵	0.003	67	0.25	0	7	7	7	1	312	0.00E+00	6.60E-04	6.60E-04	6.60E-04	0.00E+00	1.03E-04	1.03E-04	1.03E-04
CO ₂ ⁶	478.85	67	0.25	0	7	7	7	1	312	0.00E+00	1.24E+02	1.24E+02	1.24E+02	0.00E+00	1.93E+01	1.93E+01	1.93E+01

- Power rating based on technical data provided by National Railway Equipment Co.
- ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.
- SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:
 $500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lbs Sulfur} = 0.154 \text{ g/bhp-hr}$
 Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).
- A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM_{2.5} emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.
- An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.
- Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.
- Assume each train stops at each siding within its route once per round trip based on following siding locations:

Siding Name	Length (ft)	Train			
Schellville	6300	T2	T3	T4	
Burdell	6078	T2	T3	T4	
Haystack	3900	T2	T3	T4	
Petaluma	4354	T2	T3	T4	
Wilford	8350	T2	T3	T4	
Todd	4750	T2	T3	T4	
Santa Rosa	7000	T2	T3	T4	
Bailhache	3638	T2	T3		
Lytton	7025	T2	T3		
Geyerville	6492	T2	T3		
Redwood Valley	6993	T1	T2	T3	
Hopland	4175	T1	T3		

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

Solid Waste Container Transfer Operations (Yard Tractor)
BAAQMD Operations¹

Emission Factors ²		power (hp)	load factor (%)	Operational Use ³		Emissions	
Compound	(lb/hp-hr)			(hrs/day)	(hrs/yr)	(lb/day)	(ton/yr)
ROG	0.003	69	82%	5.00	1560.00	0.85	0.13
CO	0.015					4.24	0.66
NOx	0.022					6.22	0.97
SOx	0.002					0.57	0.09
PM-10	0.001					0.28	0.04
PM-2.5 ⁴	0.0009					0.26	0.04
CH ₄ ⁵	0.0009					0.27	0.04
CO ₂ ⁶	176.03					49800	7769

- 1) Solid waste handling operations are only anticipated to occur within the BAAQMD region based on prospective potential operations occurring in the souther portion of the project area.
- 2) Emission factors, horse power and load factor for a yard tractor are based on the SCAQMD CEQA guidance which provides these data for various equipment for purposes of CEQA evaluation. A general purpose utility tractor was used as the basis.
- 3) The operational use is based on assuming the yard tractor operates 5 minutes per rail car to transfer solid waste containers.
- 4) A PM-2.5 emission factor for a yard tractor or equivalent was not found in the available literature source. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM2.5 emission rate is aproximatley 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in the yard tractor since the engines operate similarly with compression ignition.
- 5) An emission factor for CH₄ was not provided in the referenced SQAQMD CEQA guidance. Therefore, CH₄ from a tractor is based on factoring the tractor CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.
- 6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the Horsepower rating of 69 hp and load factor or 82%, this equates to 176.03 lb/bhp-hr.

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

Pollutant	Emission Factor	Power ¹	Time	Stops per train	Trains		Cumulative Emissions	
	(g/bhp-hr)	(bhp)	(hr/event)	(events/day)	(trains per day)	(trains per year)	(lbs/day)	(ton/yr)
ROG ²	0.06	67	0.25	2	3	936	1.33E-02	6.22E-03
CO	0.98	67	0.25	2	3	936	2.17E-01	1.02E-01
NOx	2.88	67	0.25	2	3	936	6.38E-01	2.99E-01
SOx ³	0.154	67	0.25	2	3	936	3.41E-02	1.60E-02
PM-10 (Diesel Particulate)	0.07	67	0.25	2	3	936	1.55E-02	7.26E-03
PM-2.5 ⁴	0.06	67	0.25	2	3	936	1.43E-02	6.68E-03
CH ₄ ⁵	0.003	67	0.25	2	3	936	5.66E-04	2.65E-04
CO ₂ ⁶	478.85	67	0.25	2	3	936	1.06E+02	4.97E+01

- 1) Power rating based on technical data provided by National Railway Equipment Co.
- 2) ROG emission rates were not published for locomotive engines. Therefore, the THC emissions were conservatively assumed to be equivalent to ROG.
- 3) SOx emission factor is based on low sulfur fuel with 500ppm sulfur content allowed for locomotive use prior to 2014. Assuming all the sulfur is emitted as SO₂, this equates to an emission factor of 0.154 g/bhp-hr calculated as follows:

$$500/10^6 \times 7.08 \text{ lb/gal} \times 453.6 \text{ g/lb} \times 1 \text{ gal}/20.8 \text{ bhp-hr} \times 64.1 \text{ mol-lb SO}_2/32.1 \text{ mol-lbs Sulfur} = 0.154 \text{ g/bhp-hr}$$
 Where 7.08 lb/gal is the density of diesel fuel and 20.8 bhp-hr/gal is the EPA conversion factor (EPA420-F-97-051, December 1997).
- 4) A PM-2.5 emission factor for locomotives was not found in the available literature sources. However, based on the EMFAC2007 model for heavy duty diesel trucks, the PM_{2.5} emission rate is approximately 92% of the PM-10 emission rate. Therefore, 92% of the PM-10 emission factor was used to estimate the PM-2.5 emissions for diesel combustion in locomotives since the engines operate similarly with compression ignition.
- 5) An emission factor for CH₄ from trains was not found in the available literature from the manufacturer or EPA. Therefore, CH₄ from trains is based on factoring the train CO₂ emission factor by the ratio of CH₄ to CO₂ emissions provided by the EMFAC2007 model for Heavy Duty Diesel Trucks. This approach is considered appropriate since it is based on combustion of diesel fuel from compression ignition engines.
- 6) Emission factor for CO₂ is based on the California Climate Action Registry (CCAR) General Reporting Protocol (GRP) v2.2, March 2007, Emission Factors for Mobile Emissions, Table C.3: Carbon Dioxide Emission Factors for Transport Fuels (CA Low Sulfur Diesel) of 9.96 kg CO₂/gal. Based on the EPA Conversion value of 20.8 bhp-hr/gal of diesel for locomotives (EPA420-F-97-051), this equates to 478.85 g/bhp-hr.

PM-10 treated as diesel particulate and modeled for cancer risk based on cumulative annual emissions at a single siding. The maximum number of trains operating in a single section of track is 3 (between Lombard and Santa Rosa). Therefore, the maximum possible diesel emissions from idling trains at a siding would occur if the 3 trains stopped at the same siding for each direction of travel resulting in 6 stops per day for 6 days a week, 52 weeks a year for a total of 1872 stops a year. Assuming each stop lasts 15 minutes, the total modeled emission rate is:

$$6.96\text{E-}05 \text{ annualized emissions in g/s}$$

**Preliminary Draft Emission Estimates for
NCRA DEIR Technical Analysis**

DRAFT

Temperature and RH data by city

North Coast Air Basin

City	Temperature (F)			
	Ave Max	Ave Min	Ann Ave Max	Ann Ave Min
Willits 1 NE	85.3	32.5	69	38.9
Willits Howard Rd	88.1	30.5	66.5	40.7
Ukiah	93	35.6	73.9	43.7
Cloverdale	93.8	37.5	74.1	45.4
Healdsburg	88.9	38	73.9	46
Averages	90	35	71.5	42.9

Bay Air Basin

City	Temperature (F)			
	Ave Max	Ave Min	Ann Ave Max	Ann Ave Min
Santa Rosa	83.2	37	71.7	44.5
Petaluma	82.4	38	70.6	45.2
Sonoma	89.4	37	74	44
Averages	85	37	72.1	44.6

In accordance with BAAQMD CEQA Guidance recommended temperature basis, the Mean Summer Max for all pollutants except CO, and Mean Winter Minimum for CO, will be applied for evaluating emissions through EMFAC2007.

EMFAC2007 Output by Air Basin using above Temperatures

AUTOMOBILE IDLING EMISSIONS AT TRAIN CROSSINGS (gr/idle-hr)

Compound	NORTH COAST AIR BASIN				BAY AREA AIR BASIN			
	2009		2033		2009		2033	
	Summer	Winter	Summer	Winter	Summer	Winter	Summer	Winter
THC	1.284	1.363	1.025	1.061	0.608	0.635	0.474	0.487
ROG	1.443	1.543	1.107	1.153	0.670	0.704	0.512	0.529
CO	6.729	8.426	6.156	7.286	3.522	4.094	3.087	3.507
NOx	8.308	7.822	7.289	6.855	3.687	3.523	3.576	3.415
SOx	0.006	0.006	0.005	0.005	0.003	0.003	0.003	0.002
PM-10	0.121	0.16	0.026	0.028	0.051	0.064	0.019	0.02
PM-2.5	0.112	0.147	0.024	0.026	0.047	0.059	0.017	0.018
CO2	622.567	574.777	532.758	495.161	292.276	276.206	270.912	256.961
CH4	0.064	0.069	0.048	0.05	0.030	0.031	0.023	0.023

HEAVY HEAVY DUTY TRUCK TRAVELING EMISSIONS (45MPH) (gr/mi)

Compound	NORTH COAST AIR BASIN				BAY AREA AIR BASIN			
	2009		2033		2009		2033	
	Summer	Winter	Summer	Winter	Summer	Winter	Summer	Winter
THC	0.582	0.583	0.147	0.147	0.623	0.616	0.150	0.150
ROG	0.719	0.720	0.184	0.184	0.755	0.748	0.188	0.188
CO	4.875	5.081	1.238	1.213	5.176	5.164	1.257	1.233
NOx	12.972	16.459	1.729	2.198	13.647	16.642	1.852	2.247
SOx	0.016	0.016	0.016	0.016	0.016	0.016	0.016	0.016
PM-10	0.472	0.472	0.083	0.083	0.466	0.466	0.085	0.085
PM-2.5	0.434	0.434	0.076	0.076	0.429	0.429	0.078	0.078
CO2	1674.584	1674.584	1688.213	1688.213	1633.316	1633.316	1687.160	1687.160
CH4	0.035	0.035	0.009	0.009	0.04	0.039	0.010	0.010